



**Size Board**

<b>LENGTH</b>	1900 mm
<b>WIDTH</b>	190 mm
<b>TOTAL THICKNESS</b>	14 mm
<b>THICKNESS TOP LAYER</b>	3 mm
<b>PLANK QUANTITY</b>	Min. 7 Pl. x 1900 mm

**Size Pack**

<b>PACK LENGTH</b>	1910 mm
<b>PACK WIDTH</b>	200 mm
<b>PACK THICKNESS</b>	120 mm
<b>PACK WEIGHT</b>	24 kg
<b>LAYERS/PACK</b>	8
<b>M<sup>2</sup>/PACK</b>	2.89 m <sup>2</sup>

**Size Pallet**

<b>LENGTH PALLET</b>	1930 mm
<b>WIDTH PALLET</b>	1000 mm
<b>HEIGHT PALLET</b>	1080 mm
<b>WEIGHT PALLET</b>	975 kg
<b>PACKS/PALLET</b>	40
<b>M<sup>2</sup>/PALLET</b>	115.6 m <sup>2</sup>

**Characteristics**

**Top layer**

<b>WOOD SPECIES</b>	Oak
<b>LATIN NAME</b>	Quercus Robur
<b>GRADE</b>	CLASSIC
<b>CONSTRUCTION</b>	3-layer
<b>THICKNESS TOP LAYER</b>	3 mm
<b>STRIPS</b>	1 strip
<b>CUTTING METHOD</b>	Sawn veneer
<b>BEVEL</b>	Two long sides (0,75 mm)
<b>COLOUR FINISH</b>	Smoked Natural oiled
<b>SURFACE STRUCTURE</b>	Smooth

**Composition of the support**

<b>SUPPORT TYPE</b>	Poplar support and backing
<b>WOOD SPECIES SUPPORT</b>	Poplar
<b>SUPPORT CONSTRUCTION</b>	2-layer (Support, balancer)
<b>TOTAL THICKNESS SUPPORT</b>	11 mm
<b>ADHESION</b>	Crosswise (Casco)

**Installation**

**SYSTEM**

Tongue and groove system



**APPLICATIONS**

- Light household use
- Moderate commercial use
- Normal commercial use
- Normal household use
- Intensive commercial use

**UNDERFLOOR HEATING**

Yes

**RESANDABLE**

Resandable

## Certification

This product conforms to CE standard EN 14342:2005 + A1: 2008 - Level 4 for flooring type BS EN 13489:2002 (Wood and parquet flooring, Multilayer parquet)

- Formaldehyde emission, determined according to standard EN 13183-1: E1
- Moisture content, determined according to standard EN 13183-1: 10% (+ / -2%). Fits in dry areas with a moisture content of 50% to 60%
- Width Shrinkage, complies with standard EN 13647
- Reaction to fire, determined according to standard EN 13501-1: Dfl-S1
- Does not contain any PCP (pentachlorophenol)

---

## Technical specifications

- Hardness: N / mm<sup>2</sup> (Birrell Hardness) 3.40
- Thermal conductivity:  $\lambda$  14, 00 (W / (mk)) R = 0.11 m<sup>2</sup> K / W

Additional tests:

- Tested for delamination and stability according to standard EN1910 (cf. 15-189-BRUT CLASSIC)
- The bonding was tested according to EN311 standard (see 15-189-BRUT CLASSIC)

**LabeCo bvba**  
 Sprietstraat 326  
 B-8792 DESSELGEM  
 Tel. +32 56 540 168  
 e-mail: [info@lalegno.be](mailto:info@lalegno.be)  
 URL: [www.lalegno.be](http://www.lalegno.be)

### Declaration of performance Nr. RV-130199

Labeco BVBA herewith declares that the product described below is conform with the provisions of the Construction Products Regulation (EU) No 305/2011 if installed according to the installation instructions provided in the packaging, More information on the technical aspects and use of this product can be found on the website [www.lalegno.be](http://www.lalegno.be)

Unique identification	<b>14-CLASSIC-190-NATOLIE-DG</b>
Labeling	See CE-label and marking on the packaging
Use	Wooden flooring – multilayer parquet branded Lalegno – floor covering for indoor use.
Name and coordinates of the importer	LABECO BVBA Sprietstraat 326 8792 DESSELGEM <b>BELGIUM</b>
Name and contact address Agent	none
Activity of the notified certification body as required by the harmonized standard	In accordance with the requirements of EN 14342:2005+A1:2008
European Technical Assessment	Inapplicable

#### Declared performance

Essential characteristics	Performance	European Assessment Document
Reaction to fire	<i>Dfl – s1</i>	EN 13501-1 – EN 14342, Chapter 4, Table 1
Formaldehyde emission	<i>E1</i>	EN 717-1
Pentachlorophenol (PCP) content	<i>&lt; 5 ppm</i>	EN 14342:2005+A1:2008, Chapter 4.3
Breaking strenght	<i>NPD</i>	EN 14342:2005+A1:2008
Slipperiness	<i>NPD</i>	EN 14342:2005+A1:2008
Thermal conductivity	<i>λ 14,00(W/(mk))</i> <i>R= 0,11 m² k/w</i>	EN 14342:2005+A1:2008, Chapter 4, Table 2
Biological durability	<i>Class 1</i>	EN 14342:2005+A1:2008 – Chapter 6.3.4.8

This statement has been prepared according to method 4 of appendix ZA.2 to norm EN 14342:2005+A1:2008

The performance of the described product is consistent with the declared performance. This declaration of performance is issued under the sole responsibility of the mentioned importer.

Waregem, 25/06/2017

Signed:  
J. Labeeuw



Managing director